

4M COPPER ROD

4M COPPER ROD

USE:

- For all air conditioning work.
- Packaged in 4 m rods
- Work-hardened and dehydrated Superclean high-quality refrigeration-grade copper
- Protective caps
- Saves considerable time on-site when rods are supplied insulated

SPECIFICATIONS:

- Option to obtain rods uncoated or insulated with continuous 13 or 19 mm insulation.
- Black BLS3D0 (M1) elastomer
- Film-wrapped batches.
- Reaction to fire classification as per PV FIW 0451-cpd-2-006-0-02-01/12

TECHNICAL DATA:

Diam	Reference	Ins. Th. (mm)	Reference	Ins. Th. (mm)	Copper Th. mm
3/8	04CBI38	13	04CBI19K38	19	1
1/2	04CBI12	13	04CBI19K12	19	1
5/8	04CBI58	13	04CBI19K58	19	1
3/4	04CBI34	13	04CBI19K34	19	1
7/8	04CBI78	13	04CBI19K78	19	1
1"	04CBI100	13	04CBI19K100	19	1
1"1/8	04CBI118	13	04CBI19K118	19	1
1"3/8	04CBI138	13	04CBI19K138	19	1.24
1"5/8	04CBI158	13	1"5/8 not available		1.24

