



KOROZO

PRE- STRETCH

KOROZO HIGH QUALITY PRE-STRETCH FILM



**OUR ECONOMIC SOLUTION TO
PALLET WRAP**

PRE-STRETCH

KOROZO HIGH QUALITY PRE-STRETCH FILM



Product Specifications

- High performance puncture and tear resistance at thinner thickness
- Better holding force because of reinforced edges
- Easy to Wrap – less user energy required
- Environmental friendly and easily recyclable
- Blown Pre-stretch's dart drop is higher than cast pre-stretch film
- Blown Pre-stretch's tensile force at break is higher than cast pre-stretch film



CAST AND BLOWN MANUEL PRE-STRETCH

Available starting from 7 μ to 10 μ in various widths (400mm, 430mm, 450mm and Extended core).



CAST AND BLOWN MACHINE PRE-STRETCH

Available starting from 7 μ to 10 μ in various widths (400mm, 430mm, 450mm).

CAST PRE-STRETCH TECHNICAL SPECIFICATIONS

Properties	Values	Tolerance	Unit
Width	430	± 10	mm
Thickness	7	± 1	μm
Mechanical Properties	Values	Test Method	Unit
MD Tensile Strength at Break	>100	ASTM D882	Mpa
MD Tensile Force at Break	>15	ASTM D882	N
MD Tensile Elongation at Break	>90	ASTM D882	%
Dart Drop	>4	ASTM D1709	g/ μm

BLOWN PRE-STRETCH TECHNICAL SPECIFICATIONS

Properties	Values	Tolerance	Unit
Width	430	± 10	mm
Thickness	7	± 1	μm
Mechanical Properties	Values	Test Method	Unit
MD Tensile Strength at Break	>100	ASTM D882	Mpa
MD Tensile Force at Break	>25	ASTM D882	N
MD Tensile Elongation at Break	>100	ASTM D882	%
Dart Drop	>20	ASTM D1709	g/ μm